

DATASHEET



OP9RCD

IP66 13A 2G DP RCD Switched Socket - Type A (30mA)

www.mlaccessories.co.uk

MLA PART CODE	OP9RCD
DESCRIPTION	IP66 13A 2G DP RCD Switched Socket - Type A (30mA)
NET WEIGHT (KG)	0.798
FINISH	Black
DIMENSIONS (MM)	Height - 159 Width - 170 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP66
IK RATING	IK06
OPERATING TEMPERATURE	-5 ~ 40°C
INPUT VOLTAGE	230V 50Hz
SWITCH TYPE	Double Pole
EARTH TERMINAL	Yes
LOAD/MAX. LOAD	13A
TERMINAL TYPE	Captive
TERMINAL CAPACITY	3 x 2.5mm ² or 2 x 4.0mm ²
ADDITIONAL FEATURES	RCD tripping current (I _{Δn}): 30mA. Latching type RCD.
FUNCTION	Trip time @ I _{Δn} : 40ms
CABLE ENTRY (MM)	9 x 20, 1 x 25
CABLE GLAND INCLUDED	No
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 1363-2, BS 7288
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270821345

Date Created: 23/08/2023 11:39