

Technical Specification

Product Code: OA412AGU

Description: 10AX 2 Gang 2 Way IP66 Weatherproof Switch Unit



General Information

Dimensions (mm)	91 (W) x 106 (H) x 72.5 (D)	
Finish	Anthracite Grey	
Gasket Colour	Black	
Materials	Cover, Housing & Clip: Polycarbonate Switch Membrane: Neoprene Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Seal & Gasket: Rubber Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Back Box Knockouts - Total (mm)	5 x Ø20	
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20	Back Box Knockouts - Rear (mm) 1 x Ø20
Ingress Protection	IP66	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	5	
Standards	BS EN 60669-1 BS EN 60529	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with 13A/10AX modules in the MiniGrid Range. 