


DATASHEET



BATM4

230V 4ft 20W Modular LED Batten - 4000K

www.mlaccessories.co.uk



| MLA PART CODE | BATM4 |
|-------------------------------|--|
| DESCRIPTION | 230V 4ft 20W Modular LED Batten - 4000K |
| NET WEIGHT (KG) | 1.2 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1225 Width - 61 Projection - 70 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| IK RATING | IK08 |
| WATTAGE (W) | 20 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 2800 |
| LUMENS LIGHT SOURCE ONLY (LM) | 2850 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 136 |
| CIRCUIT WATTAGE (W) | 20.7 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| RUNNING CURRENT (A) | 0.095 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0 |
| PST-LM | 0.01 |
| BEAM ANGLE (DEGREES) | 120 |
| L70B50 LIFESPAN (HRS) | 100000 |

| | |
|--|--|
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| EMERGENCY CONVERSION KIT | MODEMKIT |
| OPERATING TEMPERATURE | -20~45°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 54-114V OUTPUT CURRENT - 350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 91.5 AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270852592 |

Date Created: 07/04/2026 20:23

