

Technical Specification

Product Code: VPAB154PL

Description: 2 Gang Unfurnished Dimmer Plate & Knobs (1600W Max) - 4 Apertures



General Information

| | |
|--|---|
| Plate Dimensions (mm) | 146 (W) x 88 (H) x 8 (D) |
| Dimensions With Gasket (mm) | 149 (W) x 91 (H) x 9 (D) |
| Plate Fixing Centres - Horizontal (mm) | 120.6 |
| Style | Victorian |
| Finish | Antique Brass |
| Gasket Colour | Black |
| Materials | Front Plate & Control Button: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel Gasket: Nylon |
| Anti Microbial Certified | No |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 10 |

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Compatible Dimmer Modules

- MD9014: 100W Dual Mode LED Dimmer Module
- MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
- MD9010: 1-10V Analogue Rotary Dimmer Module
- MD9022: 40-250W Leading Edge Dimmer Module
- MD9042: 60-400W Leading Edge Dimmer Module