

Product Code: VPBZ424

Luckinslive 438518368

Description: 10AX 4 Gang 2 Way Toggle Plate Switch



General Information

| | | |
|--|---|--|
| Dimensions (mm) | 149 (W) x 91 (H) x 40 (D) | |
| Plate Dimensions (mm) | 146 (W) x 88 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 149 (W) x 91 (H) x 9 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Victorian | |
| Finish | Matt Bronze | |
| Gasket Colour | Black | |
| Switch Finish | Matt Bronze | |
| Materials | Front Plate: Stainless Steel | Switch Front & Nut: Cast Zinc |
| | Rear Housing: Nylon | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel |
| Gasket: Nylon | | |
| Anti Microbial Certified | No | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Inductive Load Rating (AX) | 10 | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | |
| Termination Type | Screw | |
| Terminal Size (mm) | 4.9 x 4.1 | Terminal Torque Value (Nm) 1.2 |
| Terminal Capacity - Solid (mm ²) | 4 x 1.5 or 2 x 2.5 | |
| Modular Rocker Switches | Yes | |
| 2 Way Switch | Yes | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125BZ for Matt Bronze finish.

