

Product Code: VPBZ502BK

Luckinslive 438518465

Description: 50A Ingot 2 Gang (Vertical) Double Pole Plate Switch



General Information

| | | |
|--|--|--|
| Dimensions (mm) | 91 (W) x 149 (H) x 37 (D) | |
| Plate Dimensions (mm) | 88 (W) x 146 (H) x 8 (D) | |
| Dimensions With Gasket (mm) | 91 (W) x 149 (H) x 9 (D) | |
| Plate Fixing Centres - Vertical (mm) | 120.6 | |
| Style | Victorian | |
| Finish | Matt Bronze | |
| Insert Colour | Black | |
| Gasket Colour | Black | |
| Materials | Front Plate: Stainless Steel | Insert & Rear Housing: Urea |
| | Switch Cover: Stainless Steel | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel |
| | Gasket: Nylon | |
| Anti Microbial Certified | No | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 50 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø6 | |
| Terminal Capacity - Solid (mm ²) | 1 x 16 | |
| Double Pole Switch | Yes | |
| Twin Earth Terminals | Yes | |
| Product Marking | On & Off | |
| Minimum Back Box Depth (mm) | 35 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |
| Terminal Torque Value (Nm) | 2.5 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

