

**Product Code:** CMA786

**Description:** 13A 2 Gang Switched Safety Shutter Socket Outlet With Type A & C USB (4.2A) Outlets



### General Information

Plate Dimensions (mm)	146 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Rounded Profile		
Finish	Polar White		
Materials	Front Plate & Rocker Switch: Urea	Rear Housing: Nylon	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	PCB: Mixed Components	Earth Strap: Mild Steel	
Anti Microbial Certified	Yes		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type "A" & Type "C"		
USB Number Of Outputs	2	USB Charging Total Load (A)	4.2
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4		
Single Pole Switched	Yes		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Product Marking	DC, 5V 3A, 5V 2.4A max, 4.2A		
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	1
<b>Standards</b>	BS 1363-2: 2016 +A1: 2018 BS EN IEC 62368-1 BS EN 62680-1-1		

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 Independent Charging: 5V DC, 4.2A – USB Type A (2.4A), USB Type C (3A)  
 Dual Charging: 5V DC, 4.2A – USB Type A (1.2A), USB Type C (3A)