


Product Code: VPCH416BK

Luckinslive 389112130

Description: 10AX Ingot 6 Gang 2 Way Plate Switch



## General Information

Dimensions (mm)	149 (W) x 91 (H) x 25 (D)	
Plate Dimensions (mm)	146 (W) x 88 (H) x 8 (D)	
Dimensions With Gasket (mm)	149 (W) x 91 (H) x 9 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
MiniGrid Plate (Gang)	2	
MiniGrid Single Width Module Quantity	2 x 3	
MiniGrid Double Width Module Quantity	2	
Style	Victorian	
Finish	Polished Chrome	
Insert Colour	Black	
Gasket Colour	Black	
Materials	Front Plate: Stainless Steel	Insert: Urea
	Switch Cover: Stainless Steel	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	Gasket: Nylon
Anti Microbial Certified	No	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3,5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm <sup>2</sup> )	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.

