

Upgrade
Sep. 2025

Arno II

Thin profile interior batten with integrated LED

Wattage switching 

CCT switching 

Ultra-high efficiency 

- High efficiency up to 143lm/W
- Switchable wattage and CCT (3000/4000/6000K)
- Supplied with long lead of 2/3 length of the luminaire

Up to **143** 



3 3 Years
Product Warranty

1000V
Surge Protection

General Specification

Voltage 220-240Vac
50/60Hz
CRI >80
SDCM <3
L80B10 Lifetime 91000h
Power Factor >0.90
Ambient Temp -20°C to 50°C
Housing Polycarbonate



Order Code	Default Power	Alternative Power	Length	CCT	Lumen
ARN22F18	-	12W	2ft	Switchable*	1620lm (3000K) 1720lm (4000K) 1700lm (6000K)
	18W	-			2300lm (3000K) 2520lm (4000K) 2440lm (6000K)
ARN24F30	-	20W	4ft	Switchable*	2480lm (3000K) 2660lm (4000K) 2620lm (6000K)
	30W	-			3520lm (3000K) 3840lm (4000K) 3720lm (6000K)
ARN25F45	-	35W	5ft	Switchable*	4650lm (3000K) 5030lm (4000K) 4920lm (6000K)
	45W	-			5510lm (3000K) 6050lm (4000K) 5840lm (6000K)
ARN26F50	-	40W	6ft	Switchable*	5260lm (3000K) 5670lm (4000K) 5620lm (6000K)
	50W	-			6410lm (3000K) 6950lm (4000K) 6780lm (6000K)

* When CCT switchable, colour temperature switches between 3000K, 4000K & 6000K

Accessory

Type	Order Code	Description
Suspension Kit	SUS02	2 wires included, maximum 1.3m drop

Order Code

ARN22F18-SCT
ARN24F30-SCT
ARN25F45-SCT
ARN26F50-SCT

Dimensions

