



DATASHEET



BT9CTEMS

230V IP65 9W CCT Adjustable LED Bulkhead with Emergency and Sensor

www.mlaccessories.co.uk



MLA PART CODE	BT9CTEMS
DESCRIPTION	230V IP65 9W CCT Adjustable LED Bulkhead with Emergency and Sensor
NET WEIGHT (KG)	0.8
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 256 Projection - 74
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
WATTAGE (W)	9
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	665 / 760 / 700
LUMENS LIGHT SOURCE ONLY (LM)	1070
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	131
LUMENS EMERGENCY MODE (LM)	120
CIRCUIT WATTAGE (W)	8.2
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.040
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.064
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000

L70B50 LIFESPAN (HRS)	60,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Manual
OPERATING TEMPERATURE	-5~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 7.5W OUTPUT VOLTAGE - 38V OUTPUT CURRENT - 200mA POWER FACTOR - >0.85 EFFICIENCY FULL LOAD - 83.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -5 ~ 50°C CASE TEMPERATURE (Tc) - 80°C
SENSOR TYPE	Microwave
OPTIMUM DETECTION RANGE (M)	Maximum 12
SENSOR DURATION	5 seconds - 30 minutes
BATTERY TYPE	Ni-Cad
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
BATTERY INCLUDED	Yes
STANDBY POWER	0.22W
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832992752

Date Created: 05/04/2026 16:04

